

HYLOAD CLOAKED FLASHING SYSTEM**Structural Sealant****DESCRIPTION**

Hyload Structural Sealant is a multipurpose structural sealant designed for difficult bonding and sealing applications.

Hyload Structural Sealant is a non-slump, self fixturing mastic that cures with exposure to atmospheric moisture to a durable rubber bond.

Hyload Structural Sealant is tough, elastic and waterproof. It bonds aggressively to steel, aluminum, brick, concrete, ceramic, Styrofoam, many coated metal surfaces including some Kynar coated metal finishes, glass, FRP, wood, engineering plastics, coal tar and SBS modified bitumen.

PHYSICAL PROPERTIES

Specific Gravity	1.62 (13.5 lbs/gallon).
Viscosity	800,000 cps Brookfield RTV, TF spindle, 4 rpm, 70°F.
Color	Gray.
Odor	Odorless when dry.

SAFETY, STORAGE AND HANDLING INFORMATION

MSDS Sheets are available upon request.

For additional information:

Hyload, Inc.
5020 Panther Parkway
Seville, Ohio 44273

Phone: 800-457-4056

Fax: 330-769-4153

Website: www.hyloadflashing.com

PERFORMANCE PROPERTIES

Shear Strength	300psi+ (7 day ambient cure)	ASTM D-1002
Elongation at break	300%	ASTM D-412
Hardness Shore A	50 to 55 (14 day ambient cure)	ASTM C-661
Tack Free Time	35 minutes	ASTM C-679
Low Temperature Flex	- 20°F PASS	
Slump (sag)	Zero slump	ASTM C-639
Shrinkage	No measurable shrinkage (14 day cure)	ASTM D-2453
Service Temperature	- 40°F to 200°F	

**Contains No Volatile Organic Solvents.
No VOC's.**