

HYLOAD CLOAKED FLASHING SYSTEM

Flashing Membrane Adhesive



DESCRIPTION

Hyload Flashing Adhesive is a moisture cured elastomeric adhesive. It has excellent adhesion to Hyload Flashing Membrane and Hyload Cloaks, structural concrete, masonry, gypsum, metal, wood, aluminum, fiberglass (FRP), vinyl (PVC), and many coated materials. Hyload Flashing Adhesive skins over in 20 minutes. The adhesive does not contain volatile solvents and will not shrink or crack. Hyload Flashing Adhesive is safe to use with expanded polystyrene foam.

Hyload Flashing Adhesive exceeds the requirements of TTS00230C Type II Class B, ASTM C92094 and Canadian Spec CAN 19, 13M82.

The product is terra cotta (dull red) in color and is available in 10.1 oz. tubes.

USE

Hyload Flashing Adhesive is designed to provide a watertight seal between Hyload Flashing Membrane overlaps and laps between Hyload Flashing and Cloaks. The Flashing Adhesive may also be used to adhere Hyload Flashing Membrane and Cloaks to various substrates.

Hyload Flashing Adhesive is an integral part of the Hyload Flashing Cloaked System. Substitution is not allowed. Product cures slowly below 30°F.

APPLICATION

Hyload Flashing Adhesive should be applied to clean, dry and relatively smooth surfaces.

When joining 2 pieces of Hyload Flashing membrane, or joining Hyload Flashing membrane to Cloaks:

Apply two (2) 1/4" beads of adhesive approximately 1/2" and 1-1/2", respectively, from the edge of the bottom membrane along the entire width of the bottom membrane. Overlap the top membrane over the bottom membrane 2" and roll lap with steel handroller, causing excess to extrude the entire length of the overlap.

Do not remove excess adhesive.

Each 10.1 oz. tube will produce approximately 100 linear feet of 1/4" bead, or enough to form 33, 18" laps.

SAFETY, STORAGE AND HANDLING INFORMATION

Keep container tightly closed when not in use. Store at room temperature. Clean up tools and hands with waterless hand cleaner.

Caution: Uncured Adhesive Irritates Eyes. In case of contact with eyes, immediately flush with water. Call a physician. Avoid prolonged contact with skin.

For additional information:

Hyload, Inc.
5020 Panther Parkway
Seville, Ohio 44273

Phone: 800-457-4056
Fax: 330-769-4153
Website: www.hyloadflashing.com